



Product Service

CERTIFICATE

No. Z1A 18 01 29312 021

Holder of Certificate: KEMMLIT-Bauelemente GmbHMaltschachstr. 37
72144 Dußlingen
GERMANY**Certification Mark:****Product:****Screens
Partition wall systems for public sanitary
facilities****Tested
according to:**PPP 52192A:2007
AfPS GS 2014:01 PAK 3.1

The product meets the safety and health requirements of the German Product Safety Act section 20 to 22 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. See also notes overleaf.

Test report no.: 713104175**Valid until:** 2023-01-30**Date,** 2018-02-07

(Horst Kristen)

Page 1 of 2



CERTIFICATE

No. Z1A 18 01 29312 021

Model(s):

NOXX GL (glass)
NOXX NR (wet area)
NOXX TR (dry area)
NOXX smart

Parameters:

NOXX GL/NR/TR partition wall system

Height: 2135 mm (doors and wall elements)
 Ground clearance: 80 mm, height adjustable
 -5 mm / +25 mm

Cabin depth: up to 1600 mm
 Door width: 570 mm, 650 mm, 750 mm

NOXX GL: The glass elements are made of colored enamelled toughened or composite pane safety glass (ESG/VSG) with a thickness of 10 mm.

NOXX NR: Doors and walls are made of 30 mm aluminum composite elements with a special profile.

NOXX TR: Doors and walls are made of 30 mm wood material with melamine resin coating.

NOXX smart partition wall system

Height: 2000 mm or 2135 mm (doors and wall elements)
 Ground clearance: 100 mm, height adjustable
 -5 mm / +25 mm

Cabin depth: up to 1600 mm
 Door width: 570 mm, 650 mm, 750 mm

NOXX smart: Door and walls are made of 10 mm toughened safety glass.

Factory(ies):

29312